

Crimping Machines

HBBQ-2040EB (2 TON)

Features

» Precise: Crimping height can be adjusted continously, with tolerance accurately to 0.03mm.

» Quick: Match to all kinds of applicators, quick and convinient change.

» Stable: Simple structure, stable & reliable operation.

» Economical: Do work at crimp instant only and save energy.

» Quite: Low noise, suitable for home basis production.

» Safe: Special over-load protection, operate in safety.



Specifications

| Туре | HBBQ-2040EB | Adjusting Range | 10mm/6mm |
|-------------|-----------------|-------------------|-------------------------|
| Stroke | 30mm/40mm | Dimension(mm) | W325×D280×H690 |
| Pressure | 20KN | Stroke Per Minute | 160s.p.m (高速200s.p.m) |
| Shut Height | 121.7mm/135.8mm | Power supply | AC220V/50Hz |
| Weight | 75Kg | Motor Power | 750W |

HBBQ-X4040E (4 TON)

Features

» Precise: Crimping height can be adjusted continously, with tolerance accurately to 0.03mm.

» Quick: Match to all kinds of applicators, quick and convinient change.

» Stable: Simple structure, stable & reliable operation.

» Economical: Do work at crimp instant only and save energy.

» Quite: Low noise, suitable for home basis production.

» Safe: Special over-load protection, operate in safety.



Specifications

| Туре | HBBQ-X4040E | Adjusting Range | 10mm/2mm |
|-------------|-----------------|-------------------|----------------|
| Stroke | 30mm/40mm | Dimension(mm) | W360×D300×H890 |
| Pressure | 40KN | Stroke Per Minute | 160s.p.m |
| Shut Height | 121.7mm/135.8mm | Power supply | AC380V/50Hz |
| Weight | 105Kg | Motor Power | 1500W |

